

Station Lights

Clearly designate cash registers, agent stations or customer service areas!



Features & Benefits:

- Flashes to alert customers when used with our Qtrac Flashing Light Controller.
- Choose from four contemporary styles, perfect for any environment!
- Bright and highly visible to customers, lights clearly display available service stations.
- Available in varying pole lengths to accommodate any counter height.



Station Lights

Clearly designate cash registers, agent stations or customer service areas!



	95-QT4352MB 3-sided Light with Black Pole	95-QT4351MB 4-sided Light with Black Pole	95-QT4303WB Single Panel Light with Black Pole	95-QT4320 Frameless Light	95-QT4330 Wall-mounted Frameless Light	95-QT4340 Laser-etched Frameless Light	95-QT4345 Laser-etched Wall-mount Frameless Light	95-QT5501 & 95QT5502/F Wireless Light Controllers
Description	3 panels each 8" x 8" (w x h) with a 4.5" high number on each panel.	4 panels each 6" x 12" (w x h) with a 6" high number on each panel.	Case is 6" x 6.75" (w x h). Light area is 3.25" x 4.5" (w x h) with a 2.75" high number.	Light panel is 5"(w) x 5.5"(h) and mounted on 1" (h) x 5.5" (w) channel.	Light panel is 5"(w) x 5.5"(h) and mounted on 1" (h) x 5.5" (w) channel.	Light panel is 5"(w) x 7.5"(h) and mounted on 1" (h) x 5.5" (w) channel.	Light panel is 5"(w) x 7.5"(h) and mounted on 1" (h) x 5.5" (w) channel.	Wireless controller turns station lights on and off automatically. Works with most manufacturer's lights and all Lavi lights.
Options	Available with White Number on Black Casing ("black out" when turned off) or Black Number on White Casing	Available with any colored number on white casing. Various colors are available for the numbers and stripe.	Available with Black number on white panel in either Gray or Black case.	Available in white with any color number.	Available in white with any color number.	Clear panel with etched number that illuminates when lit.	Clear panel with etched number that illuminates when lit.	95-QT5501 turns station lights on and off. 95-QT5502/F toggles station lights between "lit" and "flashing".
Pole/ Mounting Details	42" long pole. 1.5" diameter. Black.	42" long pole. 1.5" diameter. Black.	Available in 12", 24", 36" or 48" long pole. 1" diameter. Wrinkle Black.	Available in 12", 24", 36" or 48" long pole. 1" diameter. Satin or Wrinkle Black finish.	Satin or Wrinkle Black finish. Arm extends light 3" from wall.	Available in 12", 24", 36" or 48" long pole. 1" diameter. Satin or Wrinkle Black finish.	Satin or Wrinkle Black finish. Arm extends light 3" from wall.	N/A
Mounting Condition	4" square base. Uses four (4) 1.5" long #5 wood screws (provided).	4" square base. Uses four (4) 1.5" long #5 wood screws (provided).	3" round base. Uses three (3) 1" long #10 particle board fasteners (provided).	2" round base. Uses three (3) 1" long #10 particle board fasteners (provided).	2" wide x 7/8" high mounting plate attaches to wall with two #8 flathead screws (not provided).	2" round base. Uses three (3) 1" long #10 particle board fasteners (provided).	2" wide x 7/8" high mounting plate attaches to wall with two #8 flathead screws (not provided).	N/A
Power	120VAC @ 60Hz Adapter using less than 12 Watts of Power when on.	120VAC @ 60Hz Adapter using less than 12 Watts of Power when on.	120VAC @ 60Hz Adapter using less than 12 Watts of Power when on.	120VAC @ 60Hz Adapter using less than 12 Watts of Power when on.	120VAC @ 60Hz Adapter using less than 12 Watts of Power when on.	120VAC @ 60Hz Adapter using less than 12 Watts of Power when on.	120VAC @ 60Hz Adapter using less than 12 Watts of Power when on.	Two outlets: Z-Wave Outlet and Pass Through. Both are NEMA 5-15 (Female) receptacles. Max Load Z-Wave Outlet: 600 Watt
On/Off Switch	Yes	Yes	Yes	Yes	No	Yes	No	Yes